



## DDZR.MH26694 Chimney Liners

[Page Bottom](#)

---

### Chimney Liners

[See General Information for Chimney Liners](#)

#### AMERICAN CHIMNEY SUPPLIES INC

MH26694

129 OSER AVE  
HAUPPAUGE, NY 11788 USA

Model ECO-PRO- FORM non-metallic chimney liner system, sizes 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, and 14 diameter. Intended for use in masonry chimneys used to vent gas fired appliances equipped with draft hoods and appliances intended for use with Type B gas vents. Max installation height is 350 ft. Suitable for installation in masonry chimneys having Zero inch clearance between combustible construction and the outer chimney surface.

Model DualFuel-PROFORM non-metallic chimney liner system, sizes 3, to 40 in. diameter. Intended for use in masonry chimneys used to vent gas/oil fired appliances equipped with draft hoods and appliances intended for use with Type B gas vents/Type L vented oil-fired. Max installation height is 350 ft. Suitable for installation in masonry chimneys having ONE inch clearance between combustible construction and the outer chimney surface.

Models "Master Flex SWF" and "Master Flex PSW", flexible, stainless steel chimney liner system.

Minimum installation clearance to combustible construction from inlet of liner system is to be that which is required for the type of vent connector and appliance being connected to the liner system.

[Last Updated](#) on 2015-05-13

---

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".